

# Tech Specs

UniFi [UISP](#) Branding

[60 GHz Wireless](#) [Wireless](#) [Fiber](#) [Wired](#) [Accessory Tech](#)

Wireless > [airFiber 11 High-Band Backhaul Radio with Dish Antenna](#)

[Datasheet](#)

[Marketing Images](#)

## airFiber AF-11

Dimensions	327 x 112 x 86 mm (12.87 x 4.41 x 3.39")
Weight	2.26 kg (5 lb)
Mounting	AF-11G35 mount compatible

## Hardware

Networking interface	(1) GbE RJ45 port (1) 10/100 MbE RJ45 port
Power method	Passive PoE (Pins 1, 2, 4, 5 (+) and Pins 7, 8, 3, 6 (-)) DC Power Block
Power supply	50V DC, 1.2A PoE Gigabit Adapter (Included)
Supported voltage range	38-56V DC
RF connectors	(4) SMA Weatherproof, Two per Chain: TX 0, RX 0 (Chain 0) and TX 1, RX 1 (Chain 1) (2) N-Type Waterproof, One per Duplexer
Operating temperature	-40 to 55° C (-40 to 131° F)
Certifications	CE, FCC, IC

## Software

Modes	SISO/MIMO* <small>* Comes with (1) High-Band Duplexer pre-installed for SISO mode. For MIMO mode, a second Duplexer is available, model AF-11-DUP-H.</small>
-------	---

## System

Max. throughput	1.2+ Gbps
Max. range	300+ km
Encryption	128-bit AES

## RF

Operating frequency*	10.7-11.7 GHz <small>*Depends on regional regulations.</small>
Max. conducted TX power*	30 dBm <small>*Depends on regional regulations.</small>
Frequency accuracy	± 1 ppm
Channel bandwidth*	3.5/5/7/10/14/20/ 28/30/40/50/56 MHz selectable** Programmable Uplink and Downlink duty cycles <small>* For region-specific details, refer to the Compliance chapter of the airFiber AF-11FX User Guide at <a href="https://ui.com/download/airfiber">ui.com/download/airfiber</a> **Channel widths may vary according to country/region regulations.</small>

## airFiber AF-11G35

<b>Dimensions</b>	811 x 811 x 460 mm (31.9 x 31.9 x 18.1")
<b>Weight</b>	Without mount: 7.14 kg (15.74 lb) With mount: 11.85 kg (26.12 lb)
<b>Wind loading</b>	1538 N @ 200 km/h (346 lbf @ 125 mph)
<b>Wind survivability</b>	200 km/h (125 mph)
<b>Mounting</b>	Pole mount
<b>Frequency</b>	10.3 to 11.7 GHz
<b>Gain</b>	35 dBi
<b>HPOL beamwidth</b>	2.5°
<b>VPOL beamwidth</b>	2.5°
<b>Maximum VSWR</b>	2:1
<b>Polarization</b>	Default: H/V After rotating OMT: ± 45°
<b>Cross-pol isolation</b>	35 dB
<b>Pattern regulatory</b>	ETSI 302 217-4-2, Class 3, FCC Cat B

[Compliance Information](#)

#### Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.