

## Tech Specs

UniFi UISP Branding

[UniFi Cloud Gateways](#)

[WiFi](#)

[Switching](#)

[Cloud Keys & Gateways](#)

[Camera Security](#)

[Door Access](#)

[Phone System](#)

[New Integrations](#)


[Accessories](#)

Switching > [Standard 24](#)

[Datasheet](#)

[Installation Guide](#)

[Marketing Images](#)



### Mechanical

**Dimensions** 442.4 x 200 x 43.7 mm (17.4 x 7.9 x 1.7")

**Weight** Without mounting brackets: 2.7 kg (6 lb)  
With mounting brackets: 2.8 kg (6.2 lb)

**Enclosure material** SGCC steel

### Hardware

**Management interface** Ethernet In-Band

**Networking interface** (24) GbE RJ45 ports  
(2) 1G SFP Ethernet ports

**Total non-blocking throughput** 26 Gbps

**Switching capacity** 52 Gbps

**Forwarding rate** 38.69 Mpps

**Power method** Universal input, 100—240V AC, 50/60 Hz

**Power supply** AC/DC, internal, 36W

**Supported voltage range** 100—240V AC

**Max. power consumption** 25W

**ESD/EMP protection** Air: ± 16kV, contact: ± 12kV

**LCM display** (1) 1.3" touchscreen

**Button** Factory reset

**Operating temperature** -5 to 45° C (23 to 113° F)

**Operating humidity** 10 to 90% noncondensing

**Certifications** CE, FCC, IC

---

## LEDs

System	Status
Ethernet	Speed/link/activity
SFP	Link/activity

---

## Application Requirements

UniFi Network	Version 7.2.94 and later
---------------	--------------------------

### Stay in Touch

[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.