


Tech Specs

UniFi UISP Branding

UniFi Cloud Gateways WiFi Switching Cloud Keys & Gateways Camera Security Door Access Phone System New Integrations Accessories

airMAX Rocket Prism 5AC

Datasheet Marketing Images



*Compatible with airMAX ac devices. **24V DC, 1A GbE PoE adapter included

Mechanical

 $88 \times 40 \times 230$ mm (3.47 \times 1.58 \times 9.06") Dimensions

400 g (14.11 oz) Weight **Enclosure material** Die-cast aluminum

Mounting Pole mounting (kit Included)

342.5 N at 200 km/h (77 lbf at 125 mph) Wind loading

Hardware

Networking interface (1) GbE RJ45 port

RF Connectors (2) RP-SMA (Waterproof)

(1) GPS (Waterproof)

Power method Passive PoE (pairs 4, 5+; 7, 8 return)

24V, 1A Gigabit PoE adapter (Included) Power supply

18-26V DC Supported voltage range

Max. power consumption

LEDs (4) Signal strength: software_adjustable to correspond to custom RSSI levels

GPS, LAN, power

RoHS compliance

ETSI300-019-1.4 Shock and vibrations

Operating temperature -40 to 80° C (-40 to 176° F) Operating humidity 5 to 95% noncondensing

Certifications CE, FCC, IC

Software

Modes Access Point, station

Channel sizes

PtP mode 10/20/30/40/50/60/80 MHz

PtMP mode 10/20/30/40 MHz

Services Web server, SNMP, SSH server, telnet , ping watchdog, DHCP, NAT, bridging, routing

Utilities airMagic, airView, antenna alignment tool, discovery utility, site survey, ping, traceroute, speed test

 Distance adjustment
 Dynamic Ack and Ackless mode

 Power adjustment
 Software adjustable UI or CLI

Security WPA2 AES only

QoS Supports packet level classification WMM and user customer level: High/Medium/Low

Statistical reporting Up time, packet errors, data rates, wireless distance, Ethernet link rate

Ubiquiti specific features 30/50/60 MHz Channels, airMAX ac mode, traffic shaping with burst support, discovery protocol, frequency band offset, Ackless mode

Operating Frequency (MHz)

Worldwide 5150-5875 MHz

USA

 U-NII-1:
 5150-5250 MHz

 U-NII-2A:
 5250-5350 MHz


 U-NII-2C:
 5470-5725 MHz

 U-NII-3
 5725-5850 MHz

Management Radio (MHz)

 Worldwide
 2412-2472 MHz

 USA
 2412-2462 MHz



Terms and Conditions | Terms of Service | Privacy Policy | Return Policy | Cookies Settings

© 2024 Ubiquiti, Inc. All rights reserved.