

Tech Specs

[UniFi](#) [UISP](#) [Branding](#)

[UniFi Cloud Gateways](#)

[WiFi](#)

[Switching](#)

[Cloud Keys & Gateways](#)

[Camera Security](#)

[Door Access](#)

[Phone System](#)

[New Integrations](#)

[Accessories](#)

[PoE+ Adapter](#)

[Datasheet](#)

[Marketing Images](#)

Specifications

| | |
|--------------------------------|---------------------------------------|
| Model | U-POE-at |
| Dimensions | 93 x 62 x 35 mm (3.66 x 2.44 x 1.38") |
| Weight | 156 g (5.5 oz) |
| Output voltage | 48V DC @ 0.65A |
| LAN activity indicator | No |
| Gigabit LAN port | Yes |
| Remote reset capability | No |
| Reset button | No |
| Rated voltage | 100—240V AC @ 50/60Hz |
| Input current | 0.75A Max. |
| Inrush current | <100A peak at 26_ |
| Efficiency | 87% |
| Output ripple | 1% max. |
| Switching frequency | 70 kHz max. |
| Line regulation | ≤ 3% |
| Load regulation | ≤ 5% |
| 2-pair powering | Pins 4, 5 (+) and 7, 8 (-) |
| 4-pair powering | No |
| AC connector | IEC-320 C6 |
| Data In / PoE | RJ45 shielded socket |
| Surge protection | Difference and common mode |
| Clamping protection | 11V data, 60V power |
| Max. surge discharge | 1500A (8/20_s) power |
| Peak pulse current | 36A (10/1000_s) data |
| Shunt capacitance | <5 pF data |
| Response time | <1 ns |
| Operating temperature | 0 to 40° C (32 to 104° F) |
| Storage temperature | -30 to 70°C (-22 to 158° F) |
| Operating humidity | 10 to 95% noncondensing |
| Certifications | CE, FCC, IC, UL |

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.