


# **Tech Specs**

UniFi UISP Branding

UniFi Cloud Gateways WiFi Switching Cloud Keys & Gateways Camera Security Door Access Phone System New Integrations Accessories

WiFi > U6 Mesh

Datasheet Installation Guide Marketing Images



\*Wall, desktop, pole mount included, ceiling mount o \*\*48V DC, 0.32A GbE PoE adapter included.

## Mechanical

Dimensions Ø48.5 x 159.5 mm (Ø1.9 x 6.28")

Weight 400 g (0.88 lb) Plastic, aluminum **Enclosure material** 

Mount materials Plastic Weatherproofing IPX5

## Hardware

Networking interface (1) GbE RJ45 port

Management interfaces Ethernet Bluetooth

Power method PoE

Power supply UniFi PoE switch

48V, 0.32A PoE adapter (included)

Supported voltage range 44—57V DC 11.4W

Max. TX power

Max. power consumption

22 dBm 2.4 GHz 5 GHz 26 dBm

МІМО

2.4 GHz 2 x 2 (UL MU-MIMO) 4 x 4 (DL/UL MU-MIMO) 5 GHz

Throughput rate

573.5 Mbps 2.4 GHz 5 GHz 4.8 Gbps

Antenna gain

2.4 GHz 3 dBi 5 GHz 5 dBi LEDs White/blue

Button Factory reset

Mounting Wall, desktop, pole mount (Included)

Ceiling mount (Optional)

Certifications CE, FCC, IC

#### Software

**WiFi standards** 802.11a/b/g

WiFi 4/WiFi 5/WiFi 6

WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)

 BSSID
 8 per radio

 VLAN
 802.1Q

Advanced QoS Per-user rate limiting

 Guest traffic isolation
 Supported

 Concurrent clients
 300+

 Zero wait DFS
 Yes\*

\*Supported with upcoming firmware versions

### **Supported Data Rates**

**802.11a** 6, 9, 12, 18, 24, 36, 48, 54 Mbps

**802.11b** 1, 2, 5.5, 11 Mbps

**802.11g** 6, 9, 12, 18, 24, 36, 48, 54 Mbps

**802.11n (WiFi 4)** 6.5 Mbps to 600 Mbps (MCS0 - MCS31, HT 20/40)

 802.11ac (WiFi 5)
 6.5 Mbps to 3.4 Gbps (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80/160)

 802.11ax (WiFi 6)
 7.3 Mbps to 4.8 Gbps (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80/160)

## **Application Requirements**

UniFi Network Version 6.2.51 and later



Terms and Conditions | Terms of Service | Privacy Policy | Return Policy | Cookies Settings

© 2024 Ubiquiti, Inc. All rights reserved.