

Tech Specs

UniFi UISP Branding

UniFi Cloud Gateways

WiFi

Switching

Cloud Keys & Gateways

Camera Security

Door Access

Phone System

New Integrations

Accessories

Access Lock Electric

Datasheet

Installation Guide

Marketing Images



*The short and long front plates are included.

Mechanical

Dimensions

Lock body: 80 x 40 x 35 mm (3.15 x 1.57 x 1.38")
Short front plate: 124 x 32 x 3 mm (4.88 x 1.26 x 0.12")
Long front plate: 202 x 36 x 3 mm (7.95 x 1.42 x 0.12")

Weight

Lock body: 185 g (6.5 oz)
Short front plate: 50 g (1.8 oz)
Long front plate: 130 g (4.6 oz)

Enclosure materials

Lock body: zinc alloy
Front plate/latches: stainless steel

Hardware

Voltage

12VDC

Current power

400mA ±10%

Wiring connection

Connect the two screw terminal separately to powered lock relay on UA-Hub: NO, COM

Lock type

Fail secure lock
Single door

Lock holding force

1,200 kg (2,645 lb)

Suitability

Wooden
Steel
Aluminum

Screw terminal

+ and -

Operating temperature

-10 to 45° C (14 to 113° F)


Operating humidity

5 - 90% noncondensing

Certifications

FCC, IC, CE

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.