

Tech Specs

UniFi [UISP](#) Branding

[60 GHz Wireless](#) [Wireless](#) [Fiber](#) [Wired](#) [Accessory Tech](#)

Fiber > [UISP Fiber XGS/XG Optical Transceiver](#)

[Datasheet](#)

[Marketing Images](#)

UACC-UF-OM-XGS

Supported media	Single-mode fiber
Connector type	(1) SC/UPC
TX wavelength	1,577nm
RX wavelength	1,270nm
TX power range	+4 to +7 dBm
RX power range	-9 to -26 dBm
Downlink data rate	10 Gbps
Uplink data rate	10 Gbps (XGS) / 2.5 Gbps (XG)
Max. power consumption	2.6W
Max. cable distance	20 km
Operating temperature	0 to 70° C (32 to 158° F)
Storage temperature	-40 to 85° C (-40 to 185° F)
Packaging	Single pack
WARNING	CLASS 1 LASER PRODUCT, IEC/EN 60825-1:2014 - Do not look into the ends of the fiber/optical cable or the SFP module while the converters are powered.

[Compliance Information](#)

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.