

UniFi Cloud Gateways WiFi Switching Cloud Keys & Gateways Camera Security Door Access Phone System New Integrations Accessories

Tech Specs

UniFi UISP Branding

WiFi > AC Pro

Datasheet Installation Guide Marketing Images





*48V DC, 0.5A GbE PoE adapter included with single unit purchases

Mechanical

 $\begin{tabular}{ll} \textbf{Dimensions} & \varnothing 196.7 \times 35 \ mm \ (\varnothing 7.7 \times 1.4") \end{tabular}$

Weight Without mount: 350 g (12.4 oz),

With mount: 450 g (15.9 oz)

Hardware

Networking interface (2) GbE RJ45 ports

Management interface Ethernet

Power method PoE

48V Passive PoE

Power supply UniFi PoE switch

48V, 0.5A PoE adapter (Included)*

*5-packs do not come with PoE adapters.

 ${\bf Supported\ voltage\ range} \qquad \qquad {\bf 44-57V\ DC}$

Max. power consumption 9W

Max. TX power

2.4 GHz 22 dBm **5 GHz** 22 dBm

МІМО

2.4 GHz 3 x 3 **5 GHz** 3 x 3

Throughput rate

2.4 GHz 450 Mbps **5 GHz** 1300 Mbps

Antenna gain

3 dBi 2 GHz 5 GHz 3 dBi

Button Factory reset

Wall/ceiling (Included) Mounting -10 to 70° C (14 to 158° F) Operating temperature Operating humidity 5 to 95% noncondensing

CE, FCC, IC

Software

Certifications

WiFi standards 802.11 a/b/g/n/ac

WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES) Wireless security

BSSID 4 per radio VLAN 802.1Q

Advanced QoS Per-user rate limiting

Guest traffic isolation Supported Power save Supported

WMM Voice, video, best effort, and background

Concurrent clients 250+

Supported Data Rates (Mbps)

802.11a 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11b 1, 2, 5.5, 11 Mbps

802.11g 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11n 6.5 Mbps to 450 Mbps (MCSO - MCS23, HT 20/40)

6.5 Mbps to 1300 Mbps (MCSO - MCS9 NSS1/2/3, VHT 20/40/80) 802.11ac



Terms and Conditions | Terms of Service | Privacy Policy | Return Policy | Cookies Settings

© 2024 Ubiquiti, Inc. All rights reserved.