


Tech Specs

UniFi UISP Branding

60 GHz Wireless Wireless Fiber Wired Accessory Tech

Fiber > UISP Fiber OLT XGS

Datasheet Installation Guide Marketing Images





Mechanical

Dimensions 442.4 x 285.6 x 43.7 mm (17.4 x 11.2 x 1.7")

Weight 5.29 kg (11.7 lb)

Enclosure material SGCC steel

Hardware

Networking interface (8) XGS/XG/GPON ports

(4) 1/10/25G SFP28 ports*

*The four SFP28 ports don't support mixed speed at 25 Gbps mode. Once one of the SFP28 ports is configured at 25 Gbps mode, the others will be limited at 25 Gbps

too. The SFP28 ports only support mixed speed when all ports are at 1 Gbps or 10 Gbps.

Management interface Ethernet out-of-band

Ethernet in-band RJ45 serial console port

Bluetooth

Memory 512 MB DDR3

Onboard flash storage 64 MB NOR + 512 MB NAND

Power method (1) Universal AC input, 100-240V AC, 50/60 Hz

Power supply (2) Hotswap AC/DC PSU

Supported voltage range 100-240V AC

Max. power consumption 70W

Button (1) Factory reset

 ${\bf Certifications} \hspace{1.5cm} {\bf CE, FCC, IC}$

LEDs

System Slow blinking white: system is booting

Fast blinking white: reset to default Blinking white/blue: system is upgrading Slow blinking blue: system is connecting to UISP

Fast blinking blue: locate system Steady white: system is ready


Steady blue: system is ready and connected to UISP

MGMT port (1) White, steady on after link is up

PON ports (8) Steady white: PON link

SFP28 ports (4) White, steady on after link is up

Compliance Information



© 2024 Ubiquiti, Inc. All rights reserved.