


## **Tech Specs**

UniFi UISP Branding

60 GHz Wireless Wireless Fiber Wired Accessory Tech

### Wired > UISP Power

Datasheet Installation Guide Marketing Images



Connect to a lead-acid battery only. Using another battery type could be hazardous.

## Mechanical

**Dimensions**  $289 \times 280 \times 52 \text{ mm (11.38} \times 11.02 \times 2.05 \text{"})$ 

**Weight** 1.4 kg (3.1 lb)

Enclosure materials Polycarbonate, acrylonitrile butadiene styrene

### Hardware

Networking interface (1) 10/100 MbE RJ45 LAN port

Management interface Ethernet In-band

Bluetooth

Power TransPort output 27V DC, 100W (with 1 power adapter)

27V DC, 200W (with 2 power adapters)

**Power method** (2) 27V DC, 4.4A power adapters (120W Power TransPort Adapter not included)

Backup power (1) 25.2V DC, 7.93A rechargeable Li-ion battery pack (included) (1) 24V DC, 8.33A lead acid battery input\* (battery not included)

\*Connect to a lead-acid battery only. Using another battery type could be hazardous.

 Max. power consumption
 3W (excludes Power TransPort output and battery charger)

 ESD/EMP protection
 Air:  $\pm$  15 kV, contact:  $\pm$  8 kV

 Operating temperature
 -5 to 40° C (23 to 104° F)

 Operating humidity
 5 to 95% non-condensing

 ${\bf Certifications} \hspace{1.5cm} {\sf CE, FCC, IC} \\$ 

# LEDs System Status RJ45 data port Link/activity Power TransPort On/Off Compatibility UISP Console Supported models UISP Router (installed with UISP Box) UISP Router Pro UISP Switch (installed with UISP Box) UISP Switch Pro Software Management application UISP: Version 1.4.5 and later

Compliance Information

