

Tech Specs

UniFi UISP Branding

UniFi Cloud Gateways

WiFi

Switching

Cloud Keys & Gateways

Camera Security

Door Access

Phone System

New Integrations

Accessories

Switching > [Flex Mini](#)

Datasheet

Installation Guide

Marketing Images



*Single-unit packages include the 5V, 1A USB-C power adapter

Mechanical

Dimensions	107.2 x 70.2 x 21.2 mm (4.2 x 2.8 x 0.8")
Weight	150 g (5.3 oz)
Enclosure material	Polycarbonate

Hardware

Management interface	Ethernet In-Band
Networking interface	(5) GbE RJ45 ports
Total non-blocking throughput	5 Gbps
Switching capacity	10 Gbps
Forwarding rate	7.44 Mpps
Power method	USB Type C, 5V PoE/PoE+, 44—57V DC, 0.05—0.04A
Power supply	5V, 1A power adapter* *Only single-unit packages include the 5V, 1A USB-C power adapter.
Supported voltage range	USB Type C: 4.7—5.3V DC PoE/PoE+: 44—57V DC
Max. power consumption	2.5W
ESD/EMP protection	Air: ± 16kV, contact: ± 12kV
Button	Factory reset
Operating temperature	-5 to 45° C (23 to 113° F)
Operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC


LEDs

System	Status
Ethernet	Speed/link/activity

Application Requirements

UniFi Network	Version 5.12.5 and later
---------------	--------------------------

Stay in Touch

[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.