

Tech Specs

[UniFi](#) [UISP](#) [Branding](#)

[UniFi Cloud Gateways](#)

[WiFi](#)

[Switching](#)

[Cloud Keys & Gateways](#)

[Camera Security](#)

[Door Access](#)

[Phone System](#)

[New Integrations](#)

[Accessories](#)

Switching > [Flex Utility](#)

[Datasheet](#)

[Marketing Images](#)

Mechanical

Dimensions

Enclosure: 249 x 218 x 60 mm (9.8 x 8.6 x 2.4")
Adapter: 118.5 x 63 x 34.7 mm (4.7 x 2.5 x 1.4")

Weight

Enclosure: 740 g (26.1 oz)
Adapter: 206 g (7.27 oz)

60W PoE Adapter

Output voltage

54V, 1.11A

Rated voltage

100-240V AC

Input current

Max. 1.5A

Efficiency

> 86%

Output ripple

200mVpp

Line regulation

< 1%

Load regulation

< 3%

4-pair powering

Pins 1, 2, 4, 5+ and Pins 3, 6, 7, 8-

Operating temperature

-20 to 60° C (-4 to 140° F)

Storage temperature

-30 to 70° C (-22 to 158° F)

Operating humidity

5 to 90%, noncondensing

Surge immunity

4kV difference and Common mode

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.