

Tech Specs

UniFi UISP Branding


[UniFi Cloud Gateways](#) [WiFi](#) [Switching](#) [Cloud Keys & Gateways](#) [Camera Security](#) [Door Access](#) [Phone System](#) [New Integrations](#) [Accessories](#)

Switching > [Lite 16 PoE](#)

[Datasheet](#)

[Installation Guide](#)

[Marketing Images](#)



Mechanical

Dimensions	191.7 x 185 x 43.7 mm (7.6 x 7.3 x 1.7")
Weight	1.2 kg (2.6 lb)
Enclosure material	Plastic

Hardware

Management interface	Ethernet In-Band
Networking interface	(16) GbE RJ45 ports
PoE interface	(8) PoE/PoE+ (Pins 1, 2+; 3, 6-)
Total non-blocking throughput	16 Gbps
Switching capacity	32 Gbps
Power method	Universal input, 100—240V AC
Power supply	AC/DC, internal, 60W
Max. power consumption	15W (Excluding PoE output)
Total available PoE	45W
Max. PoE wattage per port by PSE	PoE+: 30W
Button	Factory reset
Operating temperature	-15 to 40° C (5 to 104° F)
Operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

LEDs

System	Status
Ethernet	PoE Speed/link/activity
PoE	Link/activity

Application Requirements

UniFi Network	Version 7.2.94 and later
---------------	--------------------------

Stay in Touch

[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.