

Tech Specs

UniFi UISP Branding

[UniFi Cloud Gateways](#)

[WiFi](#)

[Switching](#)

[Cloud Keys & Gateways](#)

[Camera Security](#)

[Door Access](#)

[Phone System](#)

[New Integrations](#)


[Accessories](#)

Camera Security > [G5 Flex](#)

[Datasheet](#)

[Installation Guide](#)

[Marketing Images](#)



* Ceiling and conduit mounts sold separately.

Mechanical

Dimensions Ø48 x 107.5 mm (Ø1.9 x 4.2")

Weight 170 g (6 oz)

Enclosure material Polycarbonate

Mount material Polycarbonate

Weatherproofing IPX4

Resistance IK04

Optics

Sensor 5MP CMOS sensor

Lens Fixed focal length

View angle H: 102.4°, V: 54.9°, D: 120.6°

Night mode Built-in IR LED illumination and IR cut filter

Video

Video compression H.264

Resolution 4MP 2688 x 1512 (16:9)

Max. frame rate	30 FPS
Image settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

System

Processor	Dual-core Arm® Cortex®-A7 based chip
Networking interface	10/100 MbE RJ45 port
Max. power consumption	4W
Power method	PoE
Supported voltage range	37—57V DC
LED	R/G/B/W
Button	Factory reset
Mounting	Desktop, wall, pole, hard-ceiling (Included) Ceiling, conduit (Sold separately)
Operating temperature	-20 to 40° C (-4 to 104° F)
Operating humidity	0 to 90% noncondensing
Certifications	FCC, IC, CE


Audio

Microphone	Yes (Can be disabled)
-------------------	-----------------------

Software

Web application	UniFi Protect: Version 2.2.7 or 2.7.28 and later
Mobile app	UniFi Protect iOS™ and Android™: Version 1.10.0 and later

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.