


Tech Specs

UniFi UISP Branding

UniFi Cloud Gateways WiFi Switching Cloud Keys & Gateways Camera Security Door Access Phone System New Integrations Accessories

Cloud Keys & Gateways > Gateway Lite

Datasheet Installation Guide Marketing Images





*5V DC, 3A USB-C adapter included.

Mechanical

Dimensions 98 x 98 x 30 mm (3.9 x 3.9 x 1.2")

 Weight
 320 g (11.3 oz)

 Enclosure materials
 Polycarbonate

Hardware

Processor Dual-core ARM® Cortex®-A53 at 1 GHz

Memory information1 GB DDR3LManagement interfaceEthernet
Bluetooth 5.1

Networking interface (1) GbE RJ45 WAN port

(1) GbE RJ45 LAN port

Power method USB type C (5V/3A)

Supported voltage range 100-240V

Max. power consumption 3.83W

Operating temperature $-10 \text{ to } 40^{\circ} \text{ C } (14 \text{ to } 104^{\circ} \text{ F})$ Operating humidity 5 to 95% noncondensing

 ${\bf Certifications} \hspace{1.5cm} {\sf CE, FCC, IC} \\$

Gateway Features

Performance WiFi QoS with UniFi APs

Application, domain, and country-based QoS Application and device type identification Additional internet failover with LTE Backup Internet quality and outage reporting

Next-generation security Application-aware firewall rules

Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering VLAN/subnet-based traffic segmentation

Full stateful firewall

Advanced networking License-free SD-WAN*

WireGuard, L2TP and OpenVPN server

OpenVPN client

OpenVPN and IPsec site-to-site VPN

One-click Teleport* and Identity Enterprise VPN**

Policy-based WAN and VPN routing

DHCP relay

Customizable DHCP server

IPv6 ISP support

*When paired with a Cloud Key or Official UniFi Hosting.

**When paired with a Cloud Key.

Application Requirements

UniFi Network Version 8.0.7 and later



Terms and Conditions \parallel Terms of Service \parallel Privacy Policy \parallel Return Policy \parallel Cookies Settings

© 2024 Ubiquiti, Inc. All rights reserved.